



- Resistance range 1.00000 Ω – 1.20000 MΩ
- Resistance accuracy +/- 30 ppm
- Temperature coefficient < 1ppm/°C
- Operating voltage 200 V
- Simulation of RTD temperature sensors
- Pt simulation accuracy +/- 0.01 °C
- User defined curves (conversion tables)
- RS232 (optionally USB, IEEE488, LAN)

Model M632 is a precise resistance decade box with range from 1 Ω to 1.2 MΩ. Basic accuracy is 0.003 %. Best resolution at the lowest range is 10μΩ. Decade contains stable foil resistors with low temperature coefficient switched by low thermal voltage relays. Built-in software contains function of RTD temperature sensor simulation with parameters according to IEC (DIN) or US standards, temperature setting in degree of Celsius or Fahrenheit. Instrument can be controlled via RS232, USB, LAN or GPIB interface.

M632 is sophisticated instrument with its own recalibration procedure. The procedure enables to correct any deviation in resistance without any mechanical adjusting.

Decade box is designed for checking parameters of resistance meters, regulators and process meters that use external resistance sensors for non-electric quantity measuring.

M632 Resistance accuracy

Range / Resolution	Accuracy
1.000 00 Ω - 2.000 00 Ω	0.002 % + 2 mΩ
2.000 1 Ω - 20.000 0 Ω	
20.001 Ω - 200.000 Ω	
200.01 Ω - 2000.00 Ω	0.003 %
2.000 1 kΩ - 20.000 0 kΩ	
20.001 kΩ - 200.000 kΩ	
200.01 kΩ - 1200.00 kΩ	0.005 %

M632 Pt simulation accuracy

Temperature	Accuracy Pt10 ... Pt99	Accuracy Pt100 ... Pt20000
-200.000...0.000 °C	0.05 °C	0.01 °C
0.001...200.000 °C	0.06 °C	0.015 °C
200.001...500.000 °C	0.08 °C	0.03 °C
500.001...850.000 °C	0.1 °C	0.04 °C

M632 Frequency response

R	AC/DC difference		
	100 Hz	1 kHz	10 kHz
1 Ω	0.01 %	0.02 %	0.2 %
10 Ω	0.01 %	0.01 %	0.03 %
100 Ω	0.01 %	0.01 %	0.01 %
1 kΩ	0.01 %	0.01 %	0.1 %
10 kΩ	0.01 %	0.03 %	1 %
100 kΩ	0.1 %	1 %	
1000 kΩ	2 %		

M632 Ni simulation accuracy

Temperature	Accuracy Ni10 ... Ni99	Accuracy Ni100 ... Ni20000
-60.000...300.000 °C	0.05 °C	0.01 °C

General specification

Maximal voltage:	200 V pk
Maximal current:	500mA
Maximal load:	0.25 W
TC of used resistors:	< 1 ppm/ °C
Reaction time:	6 ms
Switching method:	Fast / Smooth / Via short / Via open
Terminals:	gold plated terminals 4mm
Remote control:	RS232 interface (optionally USB, LAN, IEEE488)
Power supply:	115/230 Vac, 50/60 Hz
Reference temperatures:	+20 °C ... +26 °C
Working temperatures:	+5 °C ... +40 °C
Storage temperatures:	-10 °C ... +50 °C
Dimensions:	W 390 mm, H 128 mm, D 310 mm
Weight:	5.2 kg

Content of delivery

M632 Precision Resistance Decade
Cable RS 232
Application software
User's manual

Ordering information – options

<i>Bus</i>	M632-V1xxx - RS232 M632-V2xxx - RS232, USB, LAN, GPIB
<i>Housing</i>	M632-Vxx0x - table version M632-Vxx1x - module 19", 3HE

Resistance

RESISTANCE		14:33:45	Function
▼ FAST			
100.000 Ω			
Output	100.000 Ω		
Specification	0.0040 %		
Max. Voltage	5.00 V		
Max. Current	50.0 mA		Menu

Temperature

PLATINUM		10:18:59	Function
▼ PT385 (90)			
▼ FAST			
100.000 °C			
Output	138.505 Ω RO 100.000 Ω		
Specification	0.015 °C		
Max. Voltage	5.88 V		
Max. Current	42.5 mA		Menu

Recalibration

CALIBRATION		Previous
Resistance	1 / 37	
Nominal resistance	1.95 Ω	Next
Requested accuracy	1 mΩ	Save
Last calibrated	07/02/2012	Close
↑ .9443810 Ω ↓		